

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局



(43) 国际公布日:
2005年6月30日(30.06.2005)

PCT

(10) 国际公布号:
WO 2005/058460 A1

(51) 国际分类号: B01D 46/00, 29/54, 29/50, 39/12

(21) 国际申请号: PCT/CN2004/001415

(22) 国际申请日: 2004年12月6日(06.12.2004)

(25) 申请语言: 中文

(26) 公布语言: 中文

(30) 优先权:
200310117410.6 2003年12月17日(17.12.2003) CN
200420083806.3 2004年9月8日(08.09.2004) CN

(71) 申请人(对除美国以外的所有指定国): 广州市新力金属有限公司(SUNNY METAL INC.) [CN/CN]; 中国广东省广州市番禺南村员岗金新路01号信箱, Guangdong 511442 (CN).

(72) 发明人: 及

(75) 发明人/申请人(仅对美国): 胡瑞华(HU, Ruibua) [CN/CN]; 中国广东省广州市番禺南村员岗金新路01号信箱, Guangdong 511442 (CN).

(74) 代理人: 广州粤高专利代理有限公司(GUANGZHOU YUEGAO PATENT AGENT LIMITED CORPORATION); 中国广东省广州市建设大马路党校大厦5楼ABC单元, Guangdong 510060 (CN).

(81) 指定国(除另有指明, 要求每一种可提供的国家保护):
AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW

(84) 指定国(除另有指明, 要求每一种可提供的地区保护):
ARIPO(BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

根据细则4.17的声明:

— 关于发明人身份(细则4.17(i))仅对美国


本国际公布:

— 包括国际检索报告。

所引用双字母代码和其它缩写符号, 请参看刊登在每期PCT公报期刊起始的“代码及缩写符号简要说明”。

(54) Title: A FLUID FILTER

(54) 发明名称: 流体过滤器



(57) Abstract: The present invention provides a fluid filter which is especially fit for filtering carbon microparticles from the off-gas of diesel engine, as well as other types of fluids. The filter in the present invention includes a plate structure and a tube structure, in which the tube structure is preferably. The tube filter is mainly composed of multilayer cylindrical corrugated tube filter elements, multilayer cylindrical plate filter elements, a central tube and a housing; in which the innermost cylinder is a plate filter element which is welded with the central tube together; and the outmost cylinder also is a plate filter element which is welded with the inner surface of the housing together. The multilayer cylindrical corrugated tube filter elements are formed zigzag alternately superposed structure with the cylindrical plate filter elements. The cylindrical platbands of the two ends of the corrugated tube filter element are welded together with the nested cylindrical plate filter elements along one edge offering a seal in zigzag fashion. The both ends of the zigzag seal are a fluid inlet point and a fluid outlet point. The filter of the present invention has a large filter area ratio and a large handling capacity, but a small volume.

[见续页]